

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

In the Claims:

1. (CURRENTLY AMENDED) A millimeter wave (MMW) radio frequency transceiver module comprising:

a substrate board;

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section; ~~and~~

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections; and

a microstrip-to-waveguide transition formed at each of the transmitter and receiver sections.

2. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, and further comprising electrical interconnects that are printed on the substrate board.

3. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, and further comprising a dielectric layer and conductive layer formed on the substrate board opposite the MMIC chips and filters and radio frequency interconnects side, and further comprising electrical interconnects formed within the conductive layer, and a plurality of conductive vias extending from the electrical interconnects through the substrate board to the

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

surface having the MMIC chips and filters and radio frequency interconnects.

4. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, and further comprising a cutout formed within the substrate for receiving a MMIC chip for allowing direct attachment of the MMIC chip to a coefficient of thermal expansion (CTE) matched carrier or heat sink.

5. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, and further comprising at least one row of ground vias formed within the substrate board and providing isolation between at least the transmitter and the receiver sections formed on the substrate board.

6. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, wherein said transmitter, receiver and local oscillator sections are formed separated and sectioned from each other to enhance isolation and reduce oscillations.

7. (CANCELLED)

8. (CURRENTLY AMENDED) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1 ~~Claim 7~~, wherein each microstrip-to-waveguide transition comprises a backshort formed relative to the substrate board and a

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

waveguide launch operative with the backshort, and a plurality of isolation vias.

9. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 1, wherein said substrate board comprises a single ceramic board.

10. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 9, wherein said single, ceramic board is from about 90 to about 99.6 percent alumina, and ranges from about 5 to about 20 mil thick.

11. (CURRENTLY AMENDED) A millimeter wave (MMW) radio frequency transceiver module comprising:

housing having a bottom plate and housing cover attached to the bottom plate

a single ceramic substrate board positioned on the bottom plate and covered by the housing cover;

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section; and

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections.

12. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, wherein the housing cover includes an electro-magnetic interference gasket that is

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

positioned above and around MMIC chips supported by substrate board.

13. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising radio frequency channels formed in the cover and an absorber material operative with the channels to enhance isolation among the local oscillator, transmitter and receiver sections.

14. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, wherein the housing cover includes SMA connectors having a solderless spring-loaded intermediate contact.

15. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising electrical interconnects that are printed on the substrate board.

16. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising a dielectric layer and conductive layer formed on the substrate board opposite the MMIC chips and filters and radio frequency interconnects, and further comprising electrical interconnects formed within the conductive layer, and a plurality of conductive vias extending from the electrical interconnects through the substrate board to the surface having the MMIC chips and thick film printed filters and radio frequency interconnect.

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

17. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising a cutout formed within the substrate for receiving a MMIC chip for allowing direct attachment of the MMIC chip to a coefficient of thermal expansion (CTE) matched carrier or heat sink.

18. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising at least one row of ground vias formed within the substrate board and providing isolation between at least the transmitter and the receiver sections formed on the substrate board.

19. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, wherein said transmitter, receiver and local oscillator sections are formed substantially separated and sectioned from each other to enhance isolation and reduce oscillations.

20. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising a microstrip-to-waveguide transition formed at each of the transmitter and receiver sections.

21. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 20, wherein each microstrip-to-waveguide transition comprises a backshort formed relative to the substrate board and a waveguide launch

In re Patent Application of:
AMMAR ET AL.
Serial No. 10/091,382
Filing Date: **March 5, 2002**

operative with the backshort, and a plurality of isolation vias.

22. (CANCELLED)

23. (CURRENTLY AMENDED) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11 ~~Claim 22~~, wherein said single ceramic board is from about 90 to about 99.6 percent alumina and ranges from about 5 to about 20 mil thick.

24. (CURRENTLY AMENDED) A method of forming a millimeter wave (MMW) radio frequency transceiver module comprising the steps of:

forming a ceramic substrate board;

mounting a plurality of microwave monolithic integrated circuit (MMIC) chips on the substrate board such that the MMIC chips are arranged in a receiver section, a transmitter section and a local oscillator section;

forming a plurality of filters, radio frequency, and electrical interconnects that are operative with the receiver, local oscillator and transmitter sections.

25. (ORIGINAL) A method according to Claim 24, and further comprising the step of forming a dielectric layer and conductive layer on the substrate board opposite the MMIC chips and filters and radio frequency interconnects, forming electrical interconnects in the conductive layer, and forming conductive vias to extend from the electrical interconnects

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

through the substrate board to the surface having the MMIC chips and filters and radio frequency interconnects.

26. (ORIGINAL) A method according to Claim 24, and further comprising the step of printing electrical interconnects on the substrate board.

27. (CURRENTLY AMENDED) A method according to Claim 24, and further comprising the step of forming the ~~substrate board~~ ~~as a~~ ceramic substrate board ~~that is~~ about 90 to about 99.6 percent alumina and about 5 to about 20 mil thick.

28. (ORIGINAL) A method according to Claim 24, and further comprising the step of forming the transmitter, receiver, and local oscillator sections separated and sectioned from each other.

29. (ORIGINAL) A method according to Claim 24, and further comprising the step of forming a microstrip-to-waveguide transition at each of the transmitter and receiver sections.

30. (ORIGINAL) A method according to Claim 24, and further comprising the step of forming ground vias to provide isolation between at least the transmitter and receiver sections.

31. (ORIGINAL) A method according to Claim 25, and further comprising the step of forming the radio frequency interconnects and filters by thick film processing techniques.

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

32. (ORIGINAL) A millimeter wave (MMW) radio transceiver module according to Claim 1, and further comprising a plurality of embedded capacitors and resistors printed on the substrate board.

33. (ORIGINAL) A millimeter wave (MMW) radio frequency transceiver module according to Claim 11, and further comprising a plurality of embedded capacitors and resistors printed on the substrate board.

Please add new Claims 34-57 as follows:

34. (NEW) A millimeter wave (MMW) radio frequency transceiver module comprising:

a single ceramic board;

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section; and

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections.

35. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, and further comprising electrical interconnects that are printed on the substrate board.

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

36. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, and further comprising a dielectric layer and conductive layer formed on the substrate board opposite the MMIC chips and filters and radio frequency interconnects side, and further comprising electrical interconnects formed within the conductive layer, and a plurality of conductive vias extending from the electrical interconnects through the substrate board to the surface having the MMIC chips and filters and radio frequency interconnects.

37. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, and further comprising a cutout formed within the substrate for receiving a MMIC chip for allowing direct attachment of the MMIC chip to a coefficient of thermal expansion (CTE) matched carrier or heat sink.

38. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, and further comprising at least one row of ground vias formed within the substrate board and providing isolation between at least the transmitter and the receiver sections formed on the substrate board.

39. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, wherein said transmitter, receiver and local oscillator sections are formed

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

separated and sectioned from each other to enhance isolation and reduce oscillations.

40. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, and further comprising a microstrip-to-waveguide transition formed at each of the transmitter and receiver sections.

41. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 40, wherein each microstrip-to-waveguide transition comprises a backshort formed relative to the substrate board and a waveguide launch operative with the backshort, and a plurality of isolation vias.

42. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 34, wherein said single, ceramic board is from about 90 to about 99.6 percent alumina, and ranges from about 5 to about 20 mil thick.

43. (NEW) A millimeter wave (MMW) radio frequency transceiver module comprising:

housing having a bottom plate and housing cover attached to the bottom plate;

a substrate board positioned on the bottom plate and covered by the housing cover;

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section;

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections; and

an electro-magnetic interference gasket on the cover that is positioned above and around MMIC chips supported by the substrate board.

44. (NEW) A millimeter wave (MMW) radio frequency transceiver module comprising:

housing having a bottom plate and housing cover attached to the bottom plate, said cover including SMA connectors having a solderless spring-loaded intermediate contact;

a substrate board positioned on the bottom plate and covered by the housing cover;

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section; and

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections.

45. (NEW) A millimeter wave (MMW) radio frequency transceiver module comprising:

housing having a bottom plate and housing cover attached to the bottom plate;

a substrate board positioned on the bottom plate and covered by the housing cover;

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

a plurality of microwave monolithic integrated circuit (MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section;

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections; and

a microstrip-to-waveguide transition formed at each of the transmitter and receiver sections.

46. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, wherein the housing cover includes an electro-magnetic interference gasket that is positioned above and around MMIC chips supported by substrate board.

47. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, and further comprising radio frequency channels formed in the cover and an absorber material operative with the channels to enhance isolation among the local oscillator, transmitter and receiver sections.

48. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, wherein the housing cover includes SMA connectors having a solderless spring-loaded intermediate contact.

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

49. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, and further comprising electrical interconnects that are printed on the substrate board.

50. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, and further comprising a dielectric layer and conductive layer formed on the substrate board opposite the MMIC chips and filters and radio frequency interconnects, and further comprising electrical interconnects formed within the conductive layer, and a plurality of conductive vias extending from the electrical interconnects through the substrate board to the surface having the MMIC chips and thick film printed filters and radio frequency interconnect.

51. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, and further comprising a cutout formed within the substrate for receiving a MMIC chip for allowing direct attachment of the MMIC chip to a coefficient of thermal expansion (CTE) matched carrier or heat sink.

52. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, and further comprising at least one row of ground vias formed within the substrate board and providing isolation between at least the transmitter and the receiver sections formed on the substrate board.

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

53. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, wherein said transmitter, receiver and local oscillator sections are formed substantially separated and sectioned from each other to enhance isolation and reduce oscillations.

54. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, wherein each microstrip-to-waveguide transition comprises a backshort formed relative to the substrate board and a waveguide launch operative with the backshort, and a plurality of isolation vias.

55. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 45, wherein said substrate board comprises a single ceramic board.

56. (NEW) A millimeter wave (MMW) radio frequency transceiver module according to Claim 55, wherein said single ceramic board is from about 90 to about 99.6 percent alumina and ranges from about 5 to about 20 mil thick.

57. (NEW) A millimeter wave (MMW) radio frequency transceiver module comprising:

housing having a bottom plate and housing cover attached to the bottom plate and including radio frequency channels in the cover and an absorber material;

a substrate board positioned on the bottom plate and covered by the housing cover;

a plurality of microwave monolithic integrated circuit

In re Patent Application of:

AMMAR ET AL.

Serial No. **10/091,382**

Filing Date: **March 5, 2002**

(MMIC) chips supported by the substrate board and arranged in a receiver section, a local oscillator section, and a transmitter section; and

a plurality of filters and radio frequency interconnects formed on the substrate board and operative with and/or connecting the receiver, local oscillator and transmitter sections, wherein isolation among the receiver, local oscillator and transmitter sections is enhanced by said radio frequency channels and absorber material.